

## Maximum Ratings

Parameters Description	Unit	Minimum	Typical	Maximum
Operation Temperature Range	°C	-	25	-
Storage Temperature Range	°C	-40	-	85
Maximum DC Voltage	V	-	-	10
Maximum Input Power	dBm	-	-	10
Source Impedance (single ended) <sup>(1)</sup>	Ω	-	50	-
Load Impedance (single ended) <sup>(1)</sup>	Ω	-	50	-
Package type & size	V			
Length x Width	mm <sup>2</sup>	-	13.3 x 6.5	-
Height	mm	-	-	1.8


## Electrical Specification

Parameters Description	Unit	Minimum	Typical	Maximum
Center Frequency (Fo)	MHz	144.85	145.00	145.15
Insertion Loss at Fo	dB	-	18.0	20.0
Group Delay Variation	nsec	-	70	150
Absolute Delay at Fo	usec	-	1.58	-
Passband Ripple Variation	dB	-	0.70	1.0
Bandwidth at -1dB	MHz	-	14.40	-
Bandwidth at -3dB	MHz	14.70	14.86	-
Bandwidth at -40dB	MHz	-	16.75	16.90
Ultimate Rejection	dB	50	55	-
Temperature Coefficient	ppm/°C	-	-72	-

**Notes :** (1) With Matching Network (Ref. Testing Environment Circuit as shown below).

Those impedances could be modified with different impedance values and/or structures, if necessary.


## Package Dimensions



- ① SAWNICS: Brand
- ② SA14514A: Model Name
- ③ X : Date Code (Year)
- ④ Y : Date Code (Month)
- ⑤ Z : Date Code (Date)
- : Index Dot

Pin Description	
A, B, C, D, F, G, H, I, J, L	Ground
K	Input
E	Output


## Testing Environment




Test Fixture & Values	
Input	L1 = 33 nH , C1 = 8 pF
Output	L2 = 33 nH , C2 = 8 pF
Source/Load Impedance	50 Ω

## Frequency Response


### Bandwidth at -1.0 dB




### Bandwidth at -3.0 dB



### Bandwidth at -40.0 dB




### Wide-Band




## Frequency Response


### Ripple Variation



### Group Delay Variation



### Smith Chart



### SWR

