

Maximum Ratings

Parameters Description	Unit	Minimum	Typical	Maximum
Operating Temperature Range	°C	-30	-	80
Storage Temperature Range	°C	-40	-	85
Maximum DC Voltage	V	-	-	10
Maximum Input Power	dBm	-	-	10
Source Impedance (single ended) ⁽¹⁾	Ω	-	50	-
Load Impedance (single ended) ⁽¹⁾	Ω	-	50	-
Package type & size	V			
Length x Width	mm ²	-	13.3 x 6.5	-
Height	mm	-	-	1.8


Electrical Specification

Parameters Description	Unit	Minimum	Typical	Maximum
Center Frequency (Fo)	MHz	-	240.0	-
Insertion Loss at Fo	dB	-	16.0	18.0
Group Delay Variation at Fo ± 7.5 MHz	nsec	-	24	80
Absolute Delay at Fo	usec	-	0.6	
Passband Ripple Variation at Fo ± 7.5 MHz	dB	-	0.38	1.00
Bandwidth at -1dB	-	16.60	16.91	-
Bandwidth at -3dB	MHz	-	18.26	-
Bandwidth at -40dB	MHz	-	23.30	25.50
Ultimate Rejection	dB	40	45	-
Temperature Coefficient	ppm/°C	-	-18	-

Notes : (1) With Matching Network (Ref. Testing Environment Circuit as shown below).

Those impedances could be modified with different impedance values and/or structures, if necessary.


Package Dimensions



- ① SAWNICS: Brand
- ② SL24016A: Model Name
- ③ X : Date Code (Year)
- ④ Y : Date Code (Month)
- ⑤ Z : Date Code (Date)
- : Index Dot

Pin Description	
A, B, C, D, F, G, H, I, J, L	Ground
K	Input
E	Output


Testing Environment




Test Fixture & Values	
Input	L1 = 12nH, C1 = 82pF
Output	L2 = 12nH, C2 = 82pF
Source/Load Impedance	50 Ω

Frequency Response


Bandwidth at -1.0 dB




Bandwidth at -3.0 dB



Bandwidth at -40 dB




Wide Band




Frequency Response


Ripple Variation $F_o \pm 7.5\text{MHz}$



Group Delay Variation $F_o \pm 7.5\text{MHz}$



Smith Chart



VSWR

