

## Maximum Ratings

Parameters Description	Unit	Minimum	Typical	Maximum
Operating Temperature Range	°C	-20	-	70
Storage Temperature Range	°C	-40	-	85
Maximum DC Voltage	V	-	-	10
Maximum Input Power	dBm	-	-	10
Source Impedance (single ended) <sup>(1)</sup>	Ω	-	50	-
Load Impedance (single ended) <sup>(1)</sup>	Ω	-	50	-
Package type & size	V			
Length x Width	mm <sup>2</sup>	-	13.3 x 6.5	-
Height	mm	-	-	1.8


## Electrical Specification

Parameters Description	Unit	Minimum	Typical	Maximum
Center Frequency (Fo)	MHz	-	60.0	-
Insertion Loss at Fo	dB	-	14.7	17.00
Amplitude Ripple within fo ±4.60 MHz	dB <sub>p-p</sub>	-	0.45	0.80
Group Delay Variation within fo ±4.60 MHz	nsec	-	40	80
Absolute Delay at Fo	µsec	-	1.66	-
Bandwidth at -1.0 dB	MHz	10.00	10.20	-
Bandwidth at -3.0 dB	MHz	-	10.67	-
Bandwidth at -25.0 dB	MHz	-	12.25	-
Bandwidth at -40.0 dB	MHz	-	12.80	13.00
<b>Relative Attenuation:</b>				
Lower Sidelobe	dB	40	50	-
Upper Sidelobe	dB	40	50	-
Temperature Coefficient	ppm/°C	-	-86	-

**Notes :** (1) With Matching Network (Ref. Testing Environment Circuit as shown below).

Those impedances could be modified with different impedance values and/or structures, if necessary.


## Package Dimensions



- ① SAWNICs: Brand
- ② SL06010B: Model Name
- ③ X : Date Code (Year)
- ④ Y : Date Code (Month)
- ⑤ Z : Date Code (Date)
- : Index Dot

Pin Description	
A, B, C, D, F, G, H, I, J, L	Ground
K	Input
E	Output

## Testing Environment




Test Fixture & Values	
Input	L1=120nH, C1=91pF
Output	L2=100nH, C2=43pF
Source/Load Impedance	50 Ω

## Frequency Response


### Bandwidth at -1.0 dB




### Bandwidth at -3.0 dB



### Bandwidth at -25.0 dB




### Bandwidth at -40.0 dB




## Frequency Response


Ripple Variation Fo±4.60MHz



Group Delay Variation Fo±4.60MHz



Smith Chart



VSWR

