

Maximum Ratings


Parameters Description	Unit	Minimum	Typical	Maximum
Operation Temperature Range	°C	-20	-	70
Storage Temperature Range	°C	-40	-	85
Maximum DC Voltage	V	-	-	10
Maximum Input Power	dBm	-	-	10
Source Impedance (single ended) ⁽¹⁾	Ω	-	50	-
Load Impedance (single ended) ⁽¹⁾	Ω	-	50	-
Package type & size	D1			
Length x Width	mm ²	-	20.0 x 9.8	-
Height	mm	-	-	1.8

Electrical Specification

Parameters Description	Unit	Minimum	Typical	Maximum
Center Frequency (Fo)	MHz	-	75.0	-
Insertion Loss at Fo	dB	-	27.5	29.0
Group Delay Variation (Fo±12.48MHz)	nsec	-	25	50
Absolute Delay at Fo	usec	-	1.98	-
Passband Ripple Variation(Fo±12.48MHz)	dB	-	0.42	0.90
Bandwidth at -1dB	MHz	25.9	26.16	-
Bandwidth at -10dB	MHz	-	27.16	-
Bandwidth at -20dB	MHz	-	27.63	-
Bandwidth at -40dB	MHz	-	28.12	28.30
Ultimate Rejection	dB	50	52	-
Temperature Coefficient	ppm/°C	-	-72	-

Notes : (1) With Matching Network (Ref. Testing Environment Circuit as shown below).
Those impedances could be modified with different impedance values and/or structures, if necessary.


Package Dimensions



- ① SAWNICS: Brand
- ② SA07526B: Model Name
- ③ X : Date Code (Year)
- ④ Y : Date Code (Month)
- ⑤ Z : Date Code (Date)
- : Index Dot

Pin Description	
A, B, C, D, F, G, H, I	Ground
J	Input
E	Output


Testing Environment




Test Fixture & Values	
Input	L1 = 120 nH
Output	L2 = 120 nH, C1=3.3pF
Source/Load Impedance	50 Ω

Frequency Response


Bandwidth at -1.0 dB




Bandwidth at -10.0 dB



Bandwidth at -20.0 dB




Bandwidth at -40.0 dB




Frequency Response


Ripple Variation $F_o \pm 12.48\text{MHz}$



Group Delay Variation $F_o \pm 12.48\text{MHz}$



Smith Chart



VSWR

